

IP CCTV / Professional IP cameras / Hikvision / Turret cameras

DS-2CD2347G2P-LSU/SL(2.8mm)(C)

HIKVISION



Features

- Hikvision
- PRO Range
- Panoramic IP Turret Camera
- 2 x 1/2.5" Progressive Scan CMOS
- 4 Megapixel (3040x1368)
- 2.8 mm Lens
- Overview 180°
- 0 Lux
- White light range 30 m
- ColorVu: color image 24 hours
- Compression H.265+ / H.265 / H.264+ / H.264
- Motion Detection 2.0
- AcuSense, false alarm filter for vehicles and persons (in Crossing Line, Area Intrusion, Entry Region, Exit Region)
- Face Capture
- WDR (130 dB)
- 3D DNR
- Alarms
- Audio
- Built-in microphone and speaker
- Siren and strobe light

- MicroSD card slot up to 256 GB
- RJ-45 10/100M BaseT
- PoE IEEE802.3af
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible
- Weatherproof IP67

Specifications

Brand	HIKVISION
Range	PRO
Image sensor	2 x 1/2.5" Progressive Scan CMOS
Maximum resolution	4 Megapixel (3040x1368)
Main Stream rate	25 fps (3040x1368)
Extra Stream rate	25 fps (1200x536, 960x432)
Compression	H.265+ / H.264+ / H.265 / H.264
Bitrate	32 Kbps ~ 8 Mbps
Lens	2.8 mm
Viewing Angle (FOV)	H: 180°, V: 81°
Range performance	38 m (D), 15 m (O), 7.5 m (R), 3.5 m (I)
Minimum illumination	Colour: 0.0005 Lux @(F1.0, AGC ON) 0 Lux with white light, range 30 m
Day/Night	ColorVu: Color image 24 hours
Alarms	1 input / 1 relay
Deterrent alarm	Siren and strobe flash integrated in the camera
Audio	1 input / 1 output Built-in microphone and speaker
Audio type	Mono
Audio Compression	G.711/G.722.1/G.726/MP2L2/PCM/MP3/AAC
Audio bit rate	64 Kbps (G.711 ulaw)/64 Kbps (G.711 alaw)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 192 Kbps (MP2L2)/8 to 320 Kbps (MP3)/16 to 64 Kbps (AAC)
Image improvements	WDR (130 dB), BLC, HLC, 3D-DNR, AGC, AWB, ROI, Mirror Function
ANR	Yes
Motion Detection	Motion detection 2.0 with human and vehicle classification applied in motion detection. * Motion detection 2.0, Facial recognition and AcuSense cannot be enabled at the same time. Enabling one function will disable the other 2 functions

Intelligent functions	AcuSense DeepLearning based technology for human and vehicle classification with false alarm reduction applied on: Line Crossing, Area Intrusion, Area Entry, and Area Exit. * Motion detection 2.0, Facial recognition and AcuSense cannot be enabled at the same time. Enabling one function will disable the other 2 functions
Facial Recognition	Face Capture * Motion detection 2.0, Facial recognition and AcuSense cannot be enabled at the same time. Enabling one function will disable the other 2 functions
Internal memory	MicroSD card slot up to 256 GB
Network interface	Ethernet 10/100M BaseT
Remote access	Web Browser, Hik-Connect Smartphone App, PC Software iVMS-4200 and Hik-Central
Interoperability	ONVIF, ISAPI
Power	DC 12 V / 880 mA / 10.5 W max. / IEEE802.3af PoE
Degree of protection	Weatherproof IP67
Material	Metallic
Temp. operation	-30° C ~ +60° C
Dimensions	Ø 140 mm x 145.6 mm (H)
Base dimensions	Ø base 140 mm / Ø between bolts 96 mm / 4 bolts
Weight	920 g