

IP CCTV / Professional IP cameras / Hikvision / Speed Domes

DS-2DE2A404IWG1-E

HIKVISION



Features

- Hikvision
- PRO Range
- Mini PTZ IP Camera
- Average speed 50°/segundo
- 1/2.8" Progressive Scan CMOS
- 4 Megapixel (2560x1440)
- 2.8~12 mm Varifocal Motorised Lens
- 4X Optical zoom
- IR Range 20 m
- Ultra Low Light Powered by DarkFighter
- Compression H.265+/H.265/H.264+/H.264
- IR Cut
- WDR (120 dB)
- 3D-DNR
- Slot for MicroSD card up to 512 GB
- Audio
- Integrated microphone
- RJ-45 10/100 BaseT
- Web interface, CMS, Smartphone & NVR
- ONVIF compatible



- Power supply output

- PoE 802.3af

- Weatherproof IP66

- Antivandalic IK10

- Surge protection 4000 V

Specifications

Brand	HIKVISION
Range	PRO
Image sensor	1/2.8" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2560x1440)
Main stream rate	25 fps (2560x1440, 1920x1080, 1280x960, 1280x720)
Extra stream rate	25 fps (704x576, 640x480, 352x288)
Compression	H.265+/ H.265 / H.264+/ H.264
Minimum illumination	Ultra Low Light (Powered by DarkFighter) Colour: 0.005 Lux @ (F1.8, AGC ON) Black and white: 0.001 Lux @ (F1.8, AGC ON) 0 lux with IR LEDs range 20 m
Lens	Motorized varifocal 2.8~12 mm (Optical Zoom 4X))
Viewing Angle (FOV)	99.4~32.8° (H), 51.7~18.4° (V), 119.9~37.5° (D)
Range performance	180 m (D), 71.4 m (O), 36 m (R), 18 m (I)
Digital zoom	16X
Electronic shutter	1/1s~1/30.000 s
Day / Night	Removable mechanical ICR filter
Image improvements	WDR (120 dB), BLC, HLC, 3D-DNR, AGC, AWB, ROI, Mirror Function, Privacy Masking
ANR	Yes
AcuSense	DeepLearning based technology for human and vehicle classification with false alarm reduction applied on: Line Crossing, Area Intrusion
Pan/Tilt Range	Horizontal: 0~355°, Vertical: 0°~90°
Manual speed	Horizontal: 0.1~50 °/s, Vertical: 0.1~50 °/s
Speed between Presets	Horizontal: 50 °/s, Vertical: 50 °/s
Preset positions	300 preset
Internal memory	MicroSD card slot up to 512 GB
Audio	1 input (Line In) / 1 output (Line Out) Built-in microphone and speaker

Audio Compression	G.711,G.722.1,G.726,MP2L2,PCM,AAC-LC
Audio bit rate	64 Kbps (G.711),16 Kbps (G.722.1), 32 at 160 Kbps (MP2L2), 16 at 64Kbps (AAC-LC),16 Kbps (G.726)
Alarms	Does not have
PTZ Control	Through network access
Network interface	Ethernet 10 / 100 BaseT
Remote access	Web Browser, Hik-Connect Smartphone App, PC Software iVMS-4200 and Hik-Central
Interoperability	ONVIF (Profiles S, G, T), ISAPI, SDK, ISUP
Power supply	DC 12 V / 9.2 W max. PoE IEEE802.3af
Power supply output	DC 12 V, 60 mA
Temp. operation	-20° C ~ +60° C
Degree of protection	Weatherproof IP66 Antivandalic IK10 Overvoltages 4000 V
Dimensions (without bracket)	Ø 130.7 mm x 103.6 mm (H)
Base dimensions	Ø base 122 mm / Ø entre tornillos 96 mm / 4 tornillos
Weight (without bracket)	560 g